



ZPMV2.E71379 Wiring, Printed - Component

Enhanced searching capability for this category can be found in UL's iQ Family of Databases (iq.ul.com).

[Page Bottom](#)

Wiring, Printed - Component

[See General Information for Wiring, Printed - Component](#)

K & F ELECTRONICS INC

33041-45 GROESBECK HWY

FRASER, MI 48026 USA

E71379

Type	Cond Width		Cond	SS/ DS/	Max	Solder		Max	Flame	Meets	C
	Min	Edge			Area	Limits	Oper	UL796		T	
	mm(in)	mm(in)	Thk	DSO	Diam	C	sec	C	Class	DSR	I
Multilayer printed wiring boards.											
2-0	0.07 (0.003)	0.07 (0.003)	18 (0.71)	DS	50.8 (2.0)	288	10	130	V-0	All	*
4-0	0.07 (0.003)	0.07 (0.003)	18 (0.71)	DS	101.6 (4.0)	288	10	130	V-0	All	*
6	0.13 (0.005)	0.38 (0.015)	16.5 (0.65)	DS	76.2 (3.0)	260	10	105	-	▲	-
B	0.05 (0.002)	0.05 (0.002)	17 (0.67) Int:68	DS	50.8 (2.0)	260	20	130	V-0	All	-
D-1	0.10 (0.004)	0.15 (0.006)	17 (0.67)	DS	30 (1.2)	260	10	105	V-0	All	-
J-2	0.10 (0.004)	0.18 (0.007)	16.5 (0.65)	DS	25.4 (1.0)	274	15	130	V-0	All	-
J-M	0.10 (0.004)	0.20 (0.008)	17 (0.67)	DS	75 (3.0)	260	10	105	V-0	All	-
M-1	0.10 (0.004)	0.15 (0.006)	17 (0.67)	DS	30 (1.2)	260	10	105	V-0	All	-
M-10	0.12 (0.005)	0.12 (0.005)	17 (0.67) Int:213	DS	76.2 (3.0)	260	10	130	V-0	All	-
M-9	0.10 (0.004)	0.15 (0.006)	17 (0.67) Int:68	DS	76.2 (3.0)	260	10	130	V-0	All	-
M-99	0.10 (0.004)	0.15 (0.006)	17 (0.67) Int:68	DS	25.4 (1.0)	260	10	130	V-0	All	-
M-V0	0.08 (0.003)	0.18 (0.007)	17 (0.67) Int:68	SS	76.2 (3.0)	260	10	105	V-0	All	-
M0-V0	0.04 (0.002)	0.07 (0.003)	17 (0.67) Int:68	SS	76.2 (3.0)	288	10	130	V-0	All	-
Single layer printed wiring boards.											
1	0.12 (0.005)	0.12 (0.005)	17 (0.67)	DS	101.6 (4.0)	274	10	130	-	-	*
1-0	0.12 (0.005)	0.12 (0.005)	17 (0.67)	DS	101.6 (4.0)	274	10	130	V-0	All	*
1V-0	0.03 (0.001)	0.03 (0.001)	16.5 (0.65)	DS	50.8 (2.0)	260	20	130	V-0	All	-
2, B	0.25 (0.010)	0.76 (0.030)	16.5 (0.65)	DS	63.5 (2.5)	260	10	130	V-0	▲	-
2V-0	0.15 (0.006)	0.05 (0.002)	16.5 (0.65)	DS	50.8 (2.0)	260	20	120	V-0	All	-
3	0.13 (0.005)	0.23 (0.009)	16.5 (0.65)	DS	76.2 (3.0)	260	10	150	V-0	All	-

3-0	0.07 (0.003)	0.17 (0.007)	34.3 (1.35)	DS	76.2 (3.0)	288	10	130	V-0	All	*
4	0.1 (0.004)	0.1 (0.004)	16.5 (0.65)	DS	304.8 (12.0)	260	10	105	V-0	-	-
5	0.13 (0.005)	0.15 (0.006)	33 (1.30)	DS	25.4 (1.0)	260	10	130	V-0	-	-
7	0.13 (0.005)	0.23 (0.009)	16.5 (0.65)	DS	76.2 (3.0)	260	10	105	V-0	-	-
A	0.25 (0.010)	0.76 (0.030)	16.5 (0.65)	DS	63.5 (2.5)	260	10	130	V-0	All	-
D-10	0.10 (0.004)	0.15 (0.006)	17 (0.67)	DS	76.2 (3.0)	260	10	130	V-0	All	-
D-9	0.10 (0.004)	0.15 (0.006)	17 (0.67)	DS	76.2 (3.0)	260	10	130	V-0	All	-
D-V0	0.08 (0.003)	0.18 (0.007)	17 (0.67)	DS	76.2 (3.0)	260	10	105	V-0	All	-
D-V0 (SS)	0.14 (0.006)	0.20 (0.008)	34 (1.34)	SS	25.4 (1.0)	260	10	130	V-0	All	-
D0-V0	0.04 (0.002)	0.07 (0.003)	17 (0.67)	DS	76.2 (3.0)	288	10	130	V-0	All	-
J-2	0.13 (0.005)	0.20 (0.008)	17 (0.67)	DS	25.4 (1.0)	260	10	130	V-0	All	-
LD	0.18 (0.007)	0.38 (0.015)	-	DS	25.4 (1.0)	274	10	130	-	-	-
LD-1	0.18 (0.007)	0.38 (0.015)	1.3 (0.05)	SS	25.4 (1.0)	260	10	130	V-0	-	-
LD-O	0.18 (0.007)	0.38 (0.015)	-	DS	25.4 (1.0)	274	10	130	V-0	-	-

* - CTI PLC is marked on individual board.



Marking: Company name or trademark and type designation. May be followed by a suffix to denote factory identification.

Last Updated on 2010-08-31

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

[Copyright © 2010 Underwriters Laboratories Inc.®](#)

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2010 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

